

Sentry Switched CDU

STV-4303 230/400V 16/32A 48xC13 with PIPS

High-Density Power Distribution

The STV-4303 Switched Cabinet Distribution Unit (CDU) provides reliable power distribution for high density applications that require 3-Phase, 16-Amp, 32-Amp power. The Switched CDU provides reliable power distribution combined with local and remote power monitoring and environmental monitoring via IP. Use the network interface to view power, temperature and humidity levels via Web browser, or receive SNMP-based alarms and email alerts when conditions exceed defined thresholds. It utilizes PIPS - Per Inlet Power Sensing - technology for 1% measurement accuracy on power and current measurements.

This switched CDU has network, serial & environmental connections located in the middle of the unit with a top power cord entry. Current displays are easily inverted via the web GUI or serial interface. These features provide flexibility whether the CDU is connected to overhead busway or under floor power.

Additional Benefits:

Branch Circuit Protection

The Sentry CDU Family meets the UL 60950-1 requirement for Branch Circuit Protections

- UL 489 rated circuit breakers
- 10 KAIC interrupt capacity for short circuit protection

PIPS - Per Input Power Sensing

Accurately measures Active Power, Apparent Power, Energy k-Wh, Power Capacity, Reactance, and Power Capacity Used using the network interface. See the aggregate current draw, in Amps, locally using the onboard LED.

Temperature and Humidity

The Switched CDU supports two external probes. Each of these probes measure both temperature and humidity. Receive SNMP-based alert notifications when conditions exceed defined thresholds.

Linking for Switched CDU (Expansion Modules)

The Switched CDU family has the capability to daisy chain units together. The Expansion Module provides the ability to link two power circuits under one IP address.

Outlet Spacing

Forty Eight IEC C13 outlets spread over the length of the CDU to more closely match the U-spacing within the cabinet. Use shorter cords to each server for better cable management.



Key Features

- > **Remote Power Management:** Power cycle individual power outlets, or groups of power outlets, to remotely reboot servers and network devices, anywhere in the world. Or, power-off unused power receptacles
- > **High Power Distribution:** 230/400V, 3-Phase Wye, 16A or 32A power input options
- > **High Density:** Single power input feed; (48) IEC C13 outlets per enclosure
- > **IP Access & Security:** Web interface, SSL, SSH, Telnet, SNMP, FTP, SNT, Syslog, RADIUS, LDAP, LDAPS, TACACS and RS-232 access
- > **Add an Expansion Module:** Connect the Switched Expansion CDU to a Master unit for power management of separate power circuits from a single IP address
- > **Environmental Monitoring:** Each Switched CDU supports two temperature & humidity probes and reports conditions thru the user interface without the need for additional IP addresses
- > **SNMP Traps:** Provide automated alerts for power and environmental conditions
- > **Input Current Monitor:** Precisely measure the aggregate current draw (in amps) on each phase. On-site verification of the input current with the LED digital display. Remote verification via browser or serial screen.
- > **Power-up Sequencing:** Prevent an in-rush power overload

Model	Available Input Voltages	Amperage	Available Input Cord	Outlets	Dimensions (L x W x D)**
STV-4303J SEV-4303J*	230/400V 3-Phase Wye 50/60Hz	16A	IEC Red 6hr 3P+N+G Plug, 10'(3m), Top Cord Entry	(48) IEC 60320/C13	1753 x 83 x 57 mm (69.0 x 3.25 x 2.25 in.)
STV-4303K SEV-4303K*	230/400V 3-Phase Wye 50/60Hz	32A	IEC Red 6hr 3P+N+G Plug, 10'(3m), Top Cord Entry	(48) IEC 60320/C13	1753 x 83 x 57 mm (69.0 x 3.25 x 2.25 in.)

*SEV part number refers to the expansion CDU

** Product depth 3.5" at each circuit breaker

Additional Features and Specifications

Agency Approvals

- > TUVGS Mark to EN 60950-1:2006 + A11
- > FCC Class A, Part 15
- > CE Mark
- > EMC to EN 55022 Class A, EN 55024, CISPR 22 Class A

Communications and Security

- > 10/100 BaseT Ethernet
- > HTTP/HTTPS
- > SSLv3/TLSv1
- > SNMPv2/v3
- > SSHv2
- > Telnet
- > RADIUS
- > LDAPv3
- > LDAPS
- > TACACS+
- > RS-232 (Serial)
- > IPv4 and IPv6

Branch Circuit Protection

- > Compliant to UL 60950-1

Accessories

- > Optional Temperature & Humidity Probe
 - EMTH-1-1 Temperature & Humidity Probe, 10 ft (3m)
- > Environmental Monitor
 - EMCU-1-1B allows up to (2) additional temperature & humidity probes, (1) water sensor, (4) dry contact closures, (1) analog-to-digital contact sensor. Includes (1) temperature/humidity probe with unit.
- > SPM (Sentry Power Manager):
 - Monitor and Manage multiple Sentry CDU's
 - Monitor and Manage all alarm conditions
 - Reporting and Trending
 - Group or Cluster outlets for reboot and power information
 - Optional Appliance or virtual version
 - SPM v5.1+ is VMware READY



VMware and VMware Ready is a registered trademark or trademark of VMware, Inc. in the United States and/or other jurisdictions

1U SPM Appliance



Expansion Module
Model Numbers

- > SEV-4303J
- > SEV-4303K



Server Technology

HEADQUARTERS - NORTH AMERICA
 Server Technology, Inc.
 1040 Sandhill Drive
 Reno, NV 89521
 United States
 1.775.284.2000 Tel
 1.775.284.2065 Fax
 sales@servertech.com
 www.servertech.com
 www.servertechblog.com

EMEA
 Fountain Court
 2 Victoria Square
 Victoria Square
 St. Albans
 AL1 3TF
 United Kingdom
 +44 (0) 1727 884733 Tel
 +44 (0) 1727 884676 Fax
 salesint@servertech.com

APAC
 Server Technology Intl
 37th Floor, Singapore Land Tower
 50 Raffles Place
 Singapore 048623
 +65 (0) 6829 7008 Tel
 +65 (0) 6234 4574 Fax
 salesint@servertech.com