

# Sentry Metered CDU

## Key Features

- > **Input Current Monitor:**  
Precisely measure the aggregate current draw (in amps) on each power circuit. On-site verification of the input current with the LED digital display.
- > **Power Distribution:** 120V
- > **Mid-Density:** Single power input feed; 24 outlets per enclosure.

## C-24V

### Mid-Density Metered Power Distribution

Increasing power demands and density in the equipment cabinet requires new functionality from your cabinet PDU. The Sentry CDU product family uniquely meets these demands.

The Sentry Cabinet Power Distribution Unit (CDU) is an intelligent PDU with local LED input current monitoring, allowing network engineers to utilize the CDU's True RMS Power Monitor to precisely measure the current (in amps) that network devices are drawing on the power circuit. As new servers and devices are added to the power drop, immediately observe its impact on the cumulative current draw. This allows the engineer to safely load each circuit to its maximum allowable load capacity without the danger of overloading the power circuit.


### Additional Benefits:



#### Branch Circuit Protection


The Sentry CDU Family meets the new UL 60950-1 requirement for branch circuit protection.

Attention! The Sentry CDU products meet the above criteria by providing overcurrent protection with UL-listed Bussman SC fuses for each branch circuit.



#### Input Current Monitoring

The CDU's exclusive True RMS current monitoring is critical to preventing overloads in high-density computing environments. LED digital displays on the CDU enclosure report the input current of each phase or branch circuit.



#### Button Mounting

All CDUs are also compatible with button & "keyhole" style mounting for cabinets. Several cabinet manufacturers are now using this method for installing power distribution units in the cabinet.



Model	Available Input Voltages	Amperage	Available Input Cord	Outlets	Dimensions (L x W x D)
C-24V1-C20M	100-120V 50/60Hz	20A	IEC 60320/C20 Power Inlet	(24) NEMA 5-20R	54.0 x 1.75 x 2.25 in. (1372 x 45 x 57 mm)
C-24V1-L30M	100-120V 50/60Hz	30A	NEMA L5-30P Cordset, 10ft (3m)	(24) NEMA 5-20R	54.0 x 1.75 x 2.25 in. (1372 x 45 x 57 mm)

## Additional Specifications

### Agency Approvals

- > US & Canada (cTUVus mark) to UL 60950-1:2003 and CAN/CSA 22.2 No. 60950-1-03
- > FCC Class A, Part 15
- > CE
- > EMC - EN 55022 Class A, EN 55024, CISPR 22 Class A

### Power Cord Options

- > PTCORD-5 IEC 60320/C19 - 5-15P (15A Straight-Blade), 10ft (3m)
- > PTCORD-6 IEC 60320/C19 - 5-20P (20A Straight-Blade), 10ft (3m)
- > PTCORD-7 IEC 60320/C19 - L5-20P (20A Twist-Lock), 10ft (3m)

### Branch Circuit Protection

- > Compliant to UL 60950-1


**Server Technology**

HEADQUARTERS - NORTH AMERICA  
 Server Technology, Inc.  
 1040 Sandhill Drive  
 Reno, NV 89521  
 United States  
 1.775.284.2000 Tel  
 1.775.284.2065 Fax  
 sales@servertech.com  
 www.servertech.com  
 www.servertechblog.com

Western Europe, Middle East and Africa  
 Server Technology  
 Fountain Court  
 2 Victoria Square  
 Victoria Street  
 St. Albans  
 AL1 3TF  
 United Kingdom  
 +44 (0) 1727 884676 Tel  
 +44 (0) 1727 220815 Fax  
 salesint@servertech.com

Central Europe, Eastern Europe and Russia  
 Niederlassung Deutschland  
 Server Technology LLC  
 42119 Wuppertal  
 Germany  
 Tel: + 49 202 693917 x 0  
 Fax: + 49 202 693917-10  
 salesint@servertech.com

APAC  
 Server Technology  
 Room 2301, 23/F, Future Plaza  
 111-113 How Ming Street,  
 Kwun Tong, Hong Kong  
 Direct line: +852 3916 2048  
 Fax Line: +852 3916 2002  
 salesint@servertech.com